



GREENLEE
COMMUNICATIONS

fiberTOOLS™

FI-100 FIBER IDENTIFIER

FAST, SIMPLE, AND RUGGED FIBER IDENTIFICATION



LOW INSERTION LOSS.

Non-intrusive low insertion loss prevents alarm conditions

EASY OPERATION.

Identifies fiber with tone detect and a clear indication of signal transmission direction

VERSATILE.

Supports all common fibers including 250µm, 900µm, 2mm, and 3mm and is able to sense light in bend insensitive fibers

FAST. ACCURATE. RELIABLE.™

USA PHONE 800.435.0786
FAX 800.451.2632

CANADA PHONE 866.384.8813
FAX 800.524.2853

INT'L PHONE +1.815.397.7070
FAX +1.815.397.9247

FI-100

FIBER IDENTIFIER

FOR PRODUCT VIDEOS, DEMONSTRATIONS
AND MORE, SCAN THIS QR CODE OR VISIT:
www.youtube.com/GreenleeDEMO



SPECIFICATIONS

Identified Wavelength Range	800-1700nm
Identified Signal Type	270Hz \pm 5%, 1kHz \pm 5%, 2kHz \pm 5%
Detector Type	1mm InGaAs
Adapter Types	<ul style="list-style-type: none"> Ø0.25 (Applicable for Bare Fiber) Ø0.9 (Applicable for Ø0.9 Cable) Ø2.0 (Applicable for Ø2.0 Cable) Ø3.0 (Applicable for Ø3.0 Cable)
Signal Indication	Left & Right LED
Signal Direction Test Range (CW/0.9mm fiber)	<ul style="list-style-type: none"> -46 to 10dBm (1310nm) -50 to 10dBm (1550nm)
Signal Power Test Range (CW/0.9mm fiber)	-50 to +10dBm
Signal Frequency Display	270Hz, 1kHz, 2kHz

Tone Detect Test Range (Average)	Ø0.9, Ø2.0, Ø3.0	-30 to 0dBm (270Hz, 1kHz)
		-25 to 0dBm (2kHz)
Insertion Loss (Typical/ Maximum)	Ø0.25	-25 to 0dBm (1kHz, 2kHz)
		-20 to 0dBm (2kHz)
Battery	AAA Alkaline (2)	
Operating Temperature	-10 to +60°C	
Storage Temperature	-25 to +70°C	
Dimension	196 X 30.5 X 27mm	
Weight	195g	
Certifications	CE, FCC, WEEE	

*Specifications subject to change without notice

ORDERING INFORMATION

CAT NO.	DESCRIPTION
FI-100-KIT	Fiber Identifier Kit
FI-100	Fiber Identifier
FI-100-250-ADAPTER	250µm Adapter
FI-100-900-ADAPTER	900µm Adapter
FI-100-2MM-ADAPTER	2mm Adapter
FI-100-2MM-ADAPTER	3mm Adapter
FI-100-CASE	Soft Carry Case
FI-100-MANUAL	Instruction Manual
FI-100-SUNSHADE	Sun Shade

FI-100 KIT contains all items shown above, instruction manual, sun shade and two AAA batteries.

DISTRIBUTOR INFORMATION:



www.greenlee.com MA6178 06/14
4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070
©2014 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA
Greenlee Textron Inc. is a subsidiary of Textron Inc.